XANTÉ

INTRODUCING! X-33™ UV PRINTER

Prints up to 24”x36”!

PRINT ON VIRTUALLY ANY MEDIA!

- CMYK + WWWW
- UP TO 2880 DPI RESOLUTION
- PRINT ON MEDIA UP TO 6 INCHES TALL
- DUAL LED LAMPS
  (Instant Ink Curing)

Adobe® PDF

iQueue WORKFLOW

US: 251.473.6502
EU: +31 (0) 26.319.3210
xante.com

BEST. EVER.

The X-UV Printer cannot be beat.

Large flatbed printers designed for signage and graphics print at high speeds but are limited by substrate thickness.
Small format printers designed for specialty items print at slower speeds and are limited by substrate length and width.

*The Xanté family of X-UV Printers do **BOTH**.*
It's the best of both worlds.

CONTACT US TODAY FOR MORE INFORMATION.

PRINT IN THE SWEET SPOT

POWERED BY iQueue

Simply Brilliant Color Workflow

INCLUDED!

FIVE WAYS TO PRINT INTENSE, BRILLIANT, PURE WHITE.

Flood, White Active Pixels, White Inactive Pixels, White Spot Color, or No White

BUILD DEPTH WITH LAYERS OF FAST-DRYING, UV-CURED INK.

Create impressive displays that grab attention or communicate important information in braille. This process is fast and renders strong, durable results.

251.473.6502

Signage • Manufacturing • Specialty Items • Industrial • Packaging

PRINT FAST.
PRINT TALL.



HIGH QUALITY SIGNAGE AT SPEEDS OVER 100 sq.ft./hour

Resolution - up to 2880 dpi
Media size - 24” x 36” x 6”
Media weight - up to 22 pounds!

BEST-IN-CLASS

XANTÉ.com

All content including X-33® is trademark Xanté Corporation. 2020. All Rights Reserved.

X-33

SPECIFICATIONS

PRINTING CAPABILITIES

Bed size:	36” x 24” (91.4cm x 60.9cm)
Imaging prep:	36” x 23.6” (91.4cm x 59.9cm)
Max. media size:	36" x 24” (91.4cm x 60.9cm)
Min. media size:	.5” x .5”
Max. print height:	6” (15.24 cm)
Media transport:	41.3” x 24” (104.9cm x 60.9cm) Vacuum bed
Print colors:	CMYK + WWWW
Resolution:	720/1080/1440/2160/2880 DPI Resolutions
UV lamp:	Dual LED, 385-415 nM, low heat curing lamps

INK AND MEDIA

Ink type:	UV, 1 liter bottles per color
Media types:	PVC plastic, styrene, wood, aluminum, metal, acrylics, coroplast, ceramics, fabric, leather, composites, paperboard, foamboard, glass, carpet, tile and more

PRINTER CONNECTIVITY

1-Gigabit Ethernet

PREPRESS SOFTWARE

Xanté iQueue Workflow:	Adobe® PostScript® 3™, Independent CMYK Density Control, Spot Color Matching, Imposition, Digital File Editing, Variable Printing, and much more

WEIGHTS, DIMENSIONS

Dimensions:	58”L x 63”W x 24”H (147 x 160 x 60cm)
Net/Gross weight:	355lbs (161kg)
Power supply:	110v or 220v 50-60hz

WORKING CONDITION

Operating temperature:	22-26°C (68°F - 78°F)
Relative humidity:	35-75RH

Adobe® PostScript® 3™

XANTÉ

US: 251.473.6502
EU: +31 (0) 26.319.3210
xante.com

iQueue Simply Brilliant Workflow (Included)

Digital Color Workflow with Advanced Color Matching and File Management Tools

©2020 Xanté Corporation. Xanté, the Xanté logo, iQueue, RightON and X-33 are registered trademarks of Xanté Corporation.
Adobe® and PostScript® are registered trademarks of Adobe Systems, Inc. All rights reserved.

02.27.2020